KERN MPE 250K100PM



High quality personal floor scale with BMI function – with approval for professional medical use in medical diagnostics, verification optional



Kategorie	
Brand	KERN
Product categoriy	Medical scale
Product group	Personal floor scale
Product family	MPE
Measuring System	
Conformity assessment possible	✓
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	250 kg
Readability [d]	0,1 kg
Resolution	2.500
Linearity	± 0,1 kg
Reproducibility	0,1 kg
Tare range	-249,9 kg
Default unit	kg
Units	kg
Units (if device is conformity assessed)	kg
Minimum weight [Min]	2 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 kg (M1)

	_ · · · ·)
Stabilization time	3 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,1 kg
Approval	
CE mark	1

Pattern approval for conformity assessment

Accuracy classeIIIVerification scale interval [e]0,1 kg	
Verification scale interval [e] 0,1 kg	
Conformity assessment possible	
ex works	
Approval according to 93/42/EEC	
(med.)	
Display	
Display type LCD	
Display backlight \checkmark	
Display digit height - smallest digit 2 mm	
Display digit height 25 mm	
Languages of the user interface Symbol language	
Construction	
Dimension display device (W×D×H) 200×55×128 mm	
Dimensions weighing platform (W×D×H) 365×360×80 mm	
Dimensions completely mounted (W×D×H) 365×570×1030 mm	
Material display housing Plastics	
Material housing steel, lacquered	
Material weighing plate plastic	
Dimensions weighing surface (W×D) 327×333 mm	
Transport wheels	
Stand height 940 mm	
Functions	
Number of keys for operation 7 5 min	
Auto-off interval(s) in mains power 30 min	
mode selectable	
15 min	
3 min	
Auto-off interval(s) in battery5 minmode/rechargeable battery mode30 min	
15 min	
PreTare function	
Tare function manual (single & multi)	
Hold function	
Function for averaging under unstable weighing conditions	
Function for BMI calculation	
Interfaces RS-232 standard	
Power Supply	
Input voltage power supply / 100 V - 240 V, 50 / 60)

Hz

power [Max]

1

KERN MPE 250K100PM



High quality personal floor scale with BMI function – with approval for professional medical use in medical diagnostics, verification optional

Input voltage device / power [Max]	12 V, 500 mA
Plug-in power supply type	Power adapter
Supplied power supply	Power supply & battery function (battery not included)
Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH
Plug-in power supply / adapter for countries - optional	EURO UK CH
Rechargeable battery optional	Rchrg. battery optional - intern
Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight on	20 h
Rechargeable battery operating time - backlight off	40 h
Battery	6×1.5 V AA
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Battery insert
Battery operating time	20 h

Environmental conditions

Humity of environment [Max]	80 %
Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping

Readability force [d] (N)	1 d
Shipping method	Parcel service
Dimensions packaging (W×D×H)	1010×290×445 mm
Net weight approx.	12 kg
Gross weight approx.	14 kg
Shipping weight	26,1 kg

Services (optional)

Article number for adjustment at the location of installation	961-249
Article number for conformity assessment	965-129
Article number for DAkkS calibration	963-129
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION



FACTORY

