KERN ABP 200-5AM



Premium analytical balance with the latest Single-Cell Generation for extremely rapid, stable weighing resultsÂ- now also as a version with automatic sliding doors



Measuring system	
Adjustment options:	Internal calibration (auto) Internal calibration (manual)
Eccentric loading at 1/3 [Max]:	0,300 mg
Linearity:	0,100 mg
Minimum weight (USP):	30 mg
Readability [d]:	0,010 mg
Repeatability:	0,015 mg 0,030 mg 0,050 mg
Resolution:	22.000.000
Stabilisation time under laboratory conditions:	8 s
Tare range:	220 g
Warm up time:	8 h
Weighing capacity [Max]:	220 g
Weighing units:	ct g mg
Display	
Display digit height (large):	1,200 cm
Technical data about verification	
Minimum load [Min]:	1 mg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes

Verification by KERN possible:	yes
Verification class:	1
Verification value [e]:	1 mg
Counting	
Counting resolution:	220000
Mininum piece weight at piece counting (Laboratory:	1 mg
Mininum piece weight at piece counting (Normal):	10 mg
Reference weight:	yes
Functions	
Capacity display:	yes
Counting function:	yes
Function to save totals:	yes
Percentage determination:	yes
Standby function:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	30 °C
Minimum ambient temperature:	10 °C
Power supply	
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH UK AUS US
Services (optional)	
DAkkS Certificate:	963-101
Verification:	965-201
Category	
Brand:	KERN
Category:	Balances
Product Group:	Analytical balance
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	382 x 585 x 535 mm
Gross weight:	12,300 kg
Net weight:	8,200 kg
Shipping method:	Parcel service

KERN ABP200-5AM



Premium analytical balance with the latest Single-Cell Generation for extremely rapid, stable weighing resultsÂ- now also as a version with automatic sliding doors

Construction	
Dimensions draft shield (WxDxH):	213 x 156 x 225 mm
Dimensions housing (WxDxH):	213 x 433 x 344 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Weighing space (WxDxH):	166 x 156 x 220 mm
Weighing surface (d):	91

Piktogramme

STANDARD



OPTION



FACTORY

