

TRIANGO 100 C DUO

TECHNICAL DATA



FITTED WITH	1 x LED module
LUMINOUS POWER	2 x 100 000 lux / 1.0 m *
COLOR RENDERING INDEX	Ra > 95
DEPTH OF ILLUMINATION	80 cm
OPERATION EQUIPMENT	Electronic converter
VOLTAGE	100 – 240 V; 50/60 Hz
CORD LENGTH	Direct power supply
LUMINAIRE BODY	Polyamide (PA)
WEIGHT (NET)	30 kg (DUO total)
POWER CONSUMPTION	2 x 40 W
USAGE	Touch panel on cardanic system
TECHNOLOGY	Single-pole secondary
BALANCE OF ARTICULATION JOINTS	Spring (weight compensation)
CLASS OF PROTECTION	I
PROTECTION RATING	IP 43 (luminaire head)
STANDARDS MET	EN 60601-1, EN 60601-2-41
SPECIAL FEATURES	Diamond optics, sterilizable handle, maintenance-free, high quality arm system, dimmable
MOUNTING	Ceiling mount, ceiling tube can be cut on site (length: 25-120 cm)
ACCESSORIES	Sterilizable handle, intermediate ceiling adapter

TREATMENT LIGHT



	lighting field / 1.0 m	lighting field / 1.0 m	color temperature	color temperature	dimmable	Order No.
	fixed value 18 cm	changeable value 18 / 23 / 28 cm	fixed value 4300 K *	changeable value 3700 / 4300 / 4700 K *		
TRIANGO 100-1 C DUO	x		x		x	D16.201.000-00811242
TRIANGO Fokus 100-3 C DUO		x		x	x	D16.202.000-00811330

LIGHT DISTRIBUTION



valid for Triango 100 with fixed lighting field / per luminaire head

TECHNICAL DRAWING

