KERN MWS 300K100M



Wheelchair platform scale with low overall height for easy access – with approval for professional, mobile medical use in medical diagnostics, verification optional



Kategorie

Brand	KERN
Product categoriy	Medical scale
Product group	Wheelchair platform scale
Product family	MWS

Measuring System

~ <i>i</i>	
Conformity assessment possible	1
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	300 kg
Readability [d]	0,1 kg
Resolution	3.000
Linearity	± 0,1 kg
Reproducibility	0,1 kg
Default unit	kg
Units	kg
Minimum weight [Min]	2 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	300 kg (M1)
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,1 kg

Approval

Letter a second	
CE mark	1
Pattern approval for conformity assessment	1
Accuracy classe	III
Verification scale interval [e]	0,1 kg
Conformity assessment possible ex works	1
Approval according to 93/42/EEC (med.)	1

Display	
Display type	LCD
Display digit height	25 mm
Languages of the user interface	Symbol language
Construction	
Dimension display device (W×D×H)	210×110×45 mm
Dimensions weighing platform (W×D×H)	910×740×65 mm
Dimensions completely mounted (W×D×H)	1158×835×60 mm
Material display housing	Plastics
Material housing	steel, lacquered
Material weighing plate	steel, lacquered
Dimensions weighing surface (W×D)	910×740 mm
Cable length	1,8 m
Display device cable length	1,85 m
Material load cell(s)	aluminium
Levelling feet adjustable	1
Wall mount	✓
Transport wheels	✓
Functions	
Number of keys for operation	20
	3 min
Auto-off interval(s) in battery	off
mode/rechargeable battery mode	4 min 5 min
	2 min
PreTare function	∠
Tare function	manual (multi)
Hold function	
Function for averaging under unstable weighing conditions	1
Function for BMI calculation	1
Interfaces	RS-232 standard
Power Supply	
Power Supply Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage power supply /	
Input voltage power supply / power [Max]	Hz

KERN MWS 300K100M



Wheelchair platform scale with low overall height for easy access – with approval for professional, mobile medical use in medical diagnostics, verification optional

Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Rechargeable battery optional	Rchrg. battery optional - intern
Rechargeable battery charging time	14 h
Rechargeable battery operating time - backlight off	45 h
Battery	6×1.5 V AA
Battery / accumulator type	NiMH
Battery operating time	50 h
Environmental conditions	
Humity of environment [Max]	80 %
Ambient temperature [Min]	5 °C
Ambient temperature [Max]	35 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C
Packing & Shipping	
Readability force [d] (N)	2 d
Shipping method	Freight
Dimensions packaging (W×D×H)	1320×950×135 mm
Net weight approx.	30 kg
Gross weight approx.	48 kg
Shipping weight	48 kg
Services (optional)	
Article number for adjustment at the location of installation	961-249
Article number for conformity assessment	965-129
Article number for DAkkS calibration	963-129
Article number for certificate of	969-517

Pictograms

STANDARD



OPTION



FACTORY



conformity (verification)