

KERN MCC 250K100M



Ergonomically optimised chair scale – with approval for professional medical use in medical diagnostics, verification optional



Conformity assessment possible ex works	✓
---	---

Approval according to 93/42/EEC (med.)	✓
--	---

Display

Display type	LCD
--------------	-----

Display backlight	✓
-------------------	---

Display digit height	25 mm
----------------------	-------

Languages of the user interface	Symbol language
---------------------------------	-----------------

Construction

Dimension display device (W×D×H)	200×130×60 mm
----------------------------------	---------------

Dimensions weighing platform (W×D×H)	502×380×410 mm
--------------------------------------	----------------

Dimensions completely mounted (W×D×H)	625×990×985 mm
---------------------------------------	----------------

Material display housing	Plastics
--------------------------	----------

Material housing	steel, lacquered
------------------	------------------

Material weighing plate	plastic
-------------------------	---------

Dimensions weighing surface (W×D)	390×360 mm
-----------------------------------	------------

Transport wheels	✓
------------------	---

Functions

Number of keys for operation	6
------------------------------	---

Auto-off interval(s) in battery mode/rechargeable battery mode	3, 5, 15, 30 min
--	------------------

Tare function	manual (single & multi)
---------------	-------------------------

Hold function	✓
---------------	---

Function for averaging under unstable weighing conditions	✓
---	---

Function for BMI calculation	✓
------------------------------	---

Power Supply

Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
--	---------------------------

Input voltage device / power [Max]	12 V, 500 mA
------------------------------------	--------------

Plug-in power supply type	Power adapter
---------------------------	---------------

Supplied power supply	Power supply & battery function (battery not included) Accu
-----------------------	--

Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH
---	------------------

Plug-in power supply / adapter for countries - optional	EURO UK CH
---	------------------

Kategorie

Brand	KERN
-------	------

Product category	Medical scale
------------------	---------------

Product group	Chair scale
---------------	-------------

Product family	MCC
----------------	-----

Measuring System

Conformity assessment possible	✓
--------------------------------	---

Construction type of the scale	Single-range balance
--------------------------------	----------------------

Weighing system	Strain gauge
-----------------	--------------

Weighing capacity [Max]	250 kg
-------------------------	--------

Readability [d]	0,1 kg
-----------------	--------

Resolution	2.500
------------	-------

Linearity	± 0,1 kg
-----------	----------

Reproducibility	0,1 kg
-----------------	--------

Tare range	249,9 kg
------------	----------

Default unit	kg
--------------	----

Units	kg
-------	----

Minimum weight [Min]	2 kg
----------------------	------

Adjustment options	Adjusting with external weight
--------------------	--------------------------------

Recommended adjusting weight	200 kg (M1)
------------------------------	-------------

Stabilization time	3 s
--------------------	-----

Warm-up time	10 min
--------------	--------

Eccentric loading at 1/3 [Max]	0,1 kg
--------------------------------	--------

Approval

CE mark	✓
---------	---

Pattern approval for conformity assessment	✓
--	---

Accuracy classe	III
-----------------	-----

Verification scale interval [e]	0,1 kg
---------------------------------	--------

KERN MCC 250K100M



Ergonomically optimised chair scale – with approval for professional medical use in medical diagnostics, verification optional

Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight on	20 h
Rechargeable battery operating time - backlight off	40 h
Battery	6×1.5 V AA
Battery / accumulator type	Alkali(-Manganese) NiMH
Battery connection	Battery insert
Battery operating time	20 h

Environmental conditions

Humidity of environment [Max]	80 %
Ambient temperature [Min]	10 °C
Ambient temperature [Max]	40 °C

Packing & Shipping

Readability force [d] (N)	2 d
Shipping method	Freight
Dimensions packaging (W×D×H)	1080×690×1080 mm
Net weight approx.	24 kg
Gross weight approx.	38 kg
Shipping weight	37,5 kg

Services (optional)

Article number for adjustment at the location of installation	961-249
Article number for conformity assessment	965-129
Article number for DAkkS calibration	963-129
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION



FACTORY

