KERN GAB15K2DNM

Checkweighing and portioning scale, also with EC type approval [M]





| Measuring system | |
|---|----------------------|
| Adjustment options: | External calibration |
| Eccentric loading at 1/3 [Max]: | 2g 5g |
| Linearity: | 2g 5g |
| Readability [d]: | 2g 5g |
| Recommended adjusting weight: | 15 kg (F2) |
| Repeatability: | 2g 5g |
| Resolution: | 3 3.000 |
| Stabilisation time under laboratory conditions: | 2 s |
| Tare range: | 14,995 kg |
| Warm up time: | 10 min 10 min |
| Weighing capacity [Max]: | 6 kg 15 kg |
| Weighing system: | Strain gauge |
| Weighing units: | g kg |

Display

Display digit height (large): 2,400 cm

| Technical data about verification | |
|---|---------|
| Minimum load [Min]: | 40 g |
| Periodic Verification for Italy: | 969-112 |
| Verification approval conforming to 2014/31/EU: | yes |
| Verification by KERN possible: | yes |
| Verification class: | III |
| Verification value [e]: | 2g 5g |

| Counting | | |
|---|--------|--|
| Counting resolution: | 30000 | |
| Mininum piece weight at piece counting (Laboratory: | 500 mg | |
| Mininum piece weight at piece counting (Normal): | 5 g | |

| Francisco - | |
|---------------------------------|---------------------------|
| Functions | |
| Counting function: | yes |
| Function to save totals: | yes |
| Percentage determination: | yes |
| Weighing with tolerance range: | yes |
| Environmental conditions | |
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | 0 °C |
| Minimum humidity: | 0 % |
| Power supply | |
| Charging time: | 12 h |
| Input voltage: | 110 V - 230 V AC |
| Mains adapter: | Mains adapter external |
| Mains adapter/adapter included: | UK EURO CH |
| Operating time (Backlight off): | 90 h |
| Operating time (Backlight on): | 40 h |
| Rechargeable battery: | Rchrg. battery optional - |

| Operating time (Backlight oil): | 90 N |
|--|----------------------------------|
| Operating time (Backlight on): | 40 h |
| Rechargeable battery: | Rchrg. battery optional - intern |
| Services (optional) | |
| Adjustment at the location of installation | :961-248 |

| , is provided the control of the con | | |
|--|---------|--|
| DAkkS Certificate: | 963-128 | |
| Verification: | 965-228 | |
| | | |


| Brand: | KERN |
|----------------|-------------|
| Category: | Balances |
| Product Group: | Bench scale |

Category

| Packaging & shipping | |
|-------------------------------|--------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 445 x 375 x 205 mm |
| Gross weight: | 4,420 kg |
| Net weight: | 3 kg |
| Shipping method: | Parcel service |

| Construction | |
|-------------------------------------|--------------------|
| Casing material: | Plastic |
| Dimensions housing (WxDxH): | 315 x 350 x 100 mm |
| Level indicator: | yes |
| Material weighing plate: | stainless steel |
| Overall dimensions mounted (WxDxH): | 315 x 350 x 125 mm |
| Revolving screw feet: | yes |
| Weighing surface (WxD): | 295 x 225 mm |

KERN GAB15K2DNM





Piktogramme

STANDARD



















OPTION







