KERN **OBE 134T241**



Our all-round compound microscope as a comprehensive digital solution for schools, training and laboratories



Category	
Brand	Optics
Product categoriy	Microscope
Product group	Digital microscope set
Product family	OBE-S

Display	
Display resolution	2048×1536

Construction	
Dimension (W×D×H)	360×235×540 mm
Optical system	Finite
Tube type	Trinocular
Tube angle of inclination	30°
Tube 360° rotation	✓
Tube type	Butterfly
Light distribution	20:80
Contrasting methods	Bright field Darkfield (optional)
Standard objectives	4× 10× 40× 100×
Lens quality	achromatic
Nosepiece screw-in locations	4
Eyepieces fixed	✓
Interpupillary distance [Min]	50 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	one-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5
Colour temperature	6000 K

Functions	
Camera - Applicable software	integrated camera software (HDMI)
Supported operating systems	Android
Memory - total size	128 GB

Interface	
Interfaces	WiFi USB 2.0 HDMI MicroSD card slot

Ocular	
Ocular field width	HWF
Eye point	High Eye Point
Ocular magnifications	10x
Ocular visual field	18 mm
Ocular diameter	23,2 mm

Illumination	
Illuminance	Transmitted light
Illumination type transmitted light	LED
Illumination intensity transmitted light	3 W
Illumination dimmable	Transmitted light
Filter possible	✓

Focussing	
Field of view [Min]	0,18 mm
Field of view [Max]	4,5 mm
Torque regulation	✓
Fine drive minimum	0,002 mm
Focusing mechanism	coaxial coarse and fine drive

Condensor	
Condensor type	Abbe
Camera	
Cameratype	Tablet camera
Camera - Resolution	5 MP
Camera - Sensor type	Sony CMOS
C	1 /0 011

Camera - Sensor size 1/2,8"

Camera - Colour depth Colour

Camera - Framerate 30 fps

Camera- Mounting types C-mount thread

Camera - Exposure method Rolling Shutter

1

KERN **OBE 134T241**



Our all-round compound microscope as a comprehensive digital solution for schools, training and laboratories

Power Supply	
Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO
Plug-in power supply / adapter for countries - optional	AUS UK US CH
Input voltage power supply / power [Max]	100 - 240 V
Power supply cable removable	removable
Input voltage device / power [Max]	5 V, 1 A

Environmental conditions	
Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Approval		
CE mark	✓	

Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	560×440×330 mm
Shipping method	Parcel service
Net weight approx.	6 kg
Gross weight approx.	8 kg
Shipping weight	16,3 kg

Product information	
GTIN/EAN number	4045761356818
REACH classification	no prohibited substances

Pictograms

STANDARD



OPTION

